

ATTENZIONE!

Prima di procedere al montaggio, assicurarsi di avere bene compreso quanto indicato dal presente foglio illustrativo .

Il non rispetto dei punti sotto riportati potrebbe compromettere il buon funzionamento della trasmissione e dei cuscinetti in essa contenuti .

 Procedere al montaggio sul veicolo del / dei Supporti per trasmiossione (A) .
Posizionare manualmente la trasmissione ed il Supporto (Cavallotto) (B) utilizzando gli spessori forniti

3) Verificare che la luce libera non superi 1 o 1.5 mm. In caso contrario procedere ad aggiungere o togliere spessori

4) Bloccare il cavallotto (B) con la vite e il dado forniti.

5) Verificare, dopo aver bloccato la trasmissione, che la stessa giri libera!

ATTENTION!

Before the installation, please read very carefully the following points.

If the following points are not correctly applied you can create problem to the transmission and the bearings contained in the some shaft.

1) Assemble on the vehicle the support/s for the transmission (A) .

2) Place manually the transmission and the support (B) using the supplied spacers .

3) Verify that the free space indicated in the above drawing don't exceed 1 or 1.5 mm. Othérwise insert or remove the spacers .

4) Lock the support (B) with the supplied bolt and nut.

5) Verify , once you have locked the transmission , that the same turn free !

